

# ベアリングホルダーセット インローダブル直接取付タイプ 丸型

Bearing Holder Set Inlay double direct installation type Circle style

2個のベアリングを使用している為、耐荷重の必要な箇所に最適です。

RoHS指令適合品




DCM

① 鋼材S45C

② 鉛フリー無電解ニッケルメッキ

Electroless Nickel plating

③ ベアリング鋼 Steel



寸法表

品番	ベアリング	L	d	D (H7) 許容差	B	H	T	dh	D1 (g7) 許容差	F.C.B	d1	d2	H1	Unit : mm
DCM	690022	25	22		6	45	8	19	27	35	8.0	4.5	4.1	141
	600022	25	26	+0.021	8	50		22	32	40				206
	620022	30	30	0	9	54		24	36	44				298
	690122	25	24		6	48		21	30	38				166
	600122	25	28		8	52	24	34	42	224				
	620122	30	32	+0.020	10	56	26	38	46	320				
	690222	25	28	+0.021	7	57	25	35	45	254				
	600222	30	32	0	9	60	28	38	48	332				
	620222	35	35		11	64	29	42	52	460				
	690422	35	37	+0.025	9	69	34	45	56	474				
	600422	40	42	0	12	77	36	50	64	591				
	620422	45	47		14	81	40	54	68	914				
	600522	40	47		12	88	41	54	72	890				
	620522	45	52		15	94	45	60	78	1,192				
	600622	40	55	+0.030	13	96	48	62	80	1,114				
	620622	50	62	0	16	104	55	70	88	1,636				
600722	50	62		14	104	55	70	88	1,515					
600822	60	68		15	114	60	78	96	2,010					