

セブンロブノブ SLK-T, SLK-NT

Seven Lobe Knobs SLK-T, SLK-NT



RoHS指令適合品



SLK-T

SLK-NT

- ノブ knob : 艶消し黒色ナイロン樹脂PA6 (ガラス繊維強化)
Glass-fiber Nylon resin
ネジ screw : 鋼材SUS22L・三価クロメート
Steel Trivalent Chromate



Unit : mm

| 品番 | D | M | φ | d | H | h | (g) |
|----------|----|-----------|------|----|----|----|-----|
| SLK-25-T | 25 | M 5×P0.8 | 8.5 | 12 | 16 | 8 | 6 |
| SLK-32-T | 32 | M 6×P1.0 | 9.0 | 14 | 20 | 10 | 9 |
| SLK-40-T | 40 | M 8×P1.25 | 14.0 | 18 | 25 | 13 | 16 |
| SLK-50-T | 50 | M10×P1.5 | 21.0 | 22 | 32 | 17 | 31 |
| SLK-63-T | 63 | M12×P1.75 | 23.0 | 26 | 40 | 21 | 60 |

| 品番 | M | φ | D | D1 | d | H | h | ht | (g) |
|-----------|-----------|----|----|----|----|----|----|----|-----|
| SLK-32-NT | M 6×P1.0 | 11 | 32 | 11 | 14 | 20 | 10 | 4 | 9 |
| SLK-40-NT | M 8×P1.25 | 14 | 40 | 14 | 18 | 25 | 13 | 4 | 17 |
| SLK-50-NT | M10×P1.5 | 15 | 50 | 18 | 22 | 32 | 17 | 5 | 33 |
| SLK-63-NT | M12×P1.75 | 20 | 63 | 22 | 26 | 40 | 21 | 5 | 60 |

注意事項 使用温度 max80℃ min-20℃

